

Reverse Osmosis System

Ecosoft MO-9



Application: farms, steam boilers, bottled water production etc.

Description: industrial reverse osmosis system for brackish water.

Advantages:

- Reliable performance with high quality components and professional engineering
- Energy saving and efficiency with DOW FILMTEC™ XLE membranes and Grundfos Blueflux® pump
- Individual project evaluation for every case
- Flexible operation within wide range of conditions with adjustable flow rates
- CE marked and confirmed to be safe in accordance with EC New Approach Directives
- Manufacturing certified in accordance with ISO 9001:2008
- Manufactured since 1999

Specifications:

Code	Model	Flow capacity*, m ³ /h	Water consumption, m ³ /h	Forward flush flow rate, m ³ /h	Power supply	Power consumption, kW	Dimensions, H x W x D, m
MO93XLWE	MO-9	9,0	12,0–15,0	16–20	400 V, 50 Hz	7,5	2,1x4,0x1,3

**At 15 °C feed water temperature, 2000 mg/L mineralization*

Main components:

- DOW FILMTEC™ XLE-440 membrane elements
- Grundfos high pressure pump with Blueflux® technology
- Polypropylene sediment filters, 5 microns, 4,5x20"
- ECOSOFT controller
- Conductivity sensor
- European automated ball valves
- Praher and John Guest fittings/pipes
- Float switch, high pressure protection, raw water and permeate pressure switches
- Wooden box packing

Options:

- Membrane rinse with permeate
- Raw water blending
- DOW FILMTEC™ ECO PRO-440, ECO PLATINUM-440 or BW30HRLE-440i membrane element